

# ImpulseRadar CrossOver CO730

ANTENNA	DUAL-CHANNEL	SINGLE-CHANNEL
<b>Technology</b>	ImpulseRadar real-time sampling	
<b>Antenna type</b>	CrossOver dual-channel	
<b>Centre frequency</b>	CH-1: 70 MHz (LF) / CH-2: 300 MHz (HF)	
<b>Channel activation</b>	CH-1 & CH-2 (LF & HF)	CH-1 (LF) or CH-2 (HF) only
<b>Signal to noise ratio (SNR)</b>	>100 dB	
<b>Significant/useful number of bits</b>	>16 bit	
<b>Scans/second</b>	>800	
<b>Survey speed</b>	> 130 km/h @ 5 cm point interval	
<b>Time window</b>	2500 ns (LF) / 625 ns (HF)	
<b>Bandwidth</b>	>120%, fractional, -10 dB	
<b>Acquisition mode</b>	Wheel, time or manual	
<b>Positioning</b>	Wheel encoder, internal DGPS, external GPS (NMEA 0183 protocol)	
<b>Power supply</b>	12 V Li-Ion rechargeable battery, or ext. 12 V DC source (optional)	
<b>Power consumption</b>	1.5 A	1.2 A
<b>Operating time</b>	6 hours	8 hours
<b>Dimensions</b>	960 x 760 x 270 mm	
<b>Weight</b>	20.2 kg (including battery)	
<b>Operating temperature</b>	-20° to +50°C	
<b>Environmental</b>	IP65	
<b>Regulatory certification</b>	CE & FCC	
USER INTERFACE		
<b>Display</b>	720 x 1280 pixel or better	
<b>Operating system</b>	Android™ (>ver. 10) or later	
<b>Memory</b>	2.7 GB SDRAM or better	
<b>Processor</b>	Intel Atom x5-Z8550, Quad core 2.3 GHz Krait 400 or better	
<b>Recommendation</b>	Panasonic Toughpad FZ-A2 (or equivalent)	

<sup>1</sup> Cart, skid plate and display holder

<sup>2</sup> Cart, skid plate, antenna, display holder\* and display (\* 10" as per recommended Panasonic Toughpad FZ-A2)

ImpulseRadar products are under continuous development and we reserve the right to change specifications at any time and without prior notice. You may verify product specifications at any time by contacting our headquarters using the details listed below.